



03/30/00

LAW OFFICES

FREILICH, HORNBAKER & ROSEN

PROFESSIONAL CORPORATION

ARTHUR FREILICH
ROBERT D. HORNBAKER
LEON D. ROSEN
TIMOTHY T. TYSON

10960 WILSHIRE BOULEVARD, SUITE 1220

LOS ANGELES, CA 90024

TEL. (310) 477-0578 • FAX (310) 473-9277

E-MAIL timtyson@pacbell.net

jc511 U.S. PTO

09/538323



03/30/00

PATENTS, TRADEMARKS & RELATED INTELLECTUAL PROPERTY MATTERS

Patent Application
Assistant Commissioner for Patents
Washington, DC 20231

Docket No. 20/118

Enclosed for filing is the Utility Patent Application entitled
A WARNING SYSTEM by Roger E. Skoff

- ☒ Enclosed are 2 sheets of drawings.
☒ Enclosed are 16 pages of specification.
☒ Enclosed is a Declaration.
☒ Enclosed is a Verified Statement for small entity status.
☐ Enclosed is an Assignment for recordation
☐ Please transfer Disclosure Document No. dated _ to this file.
☐ Enclosed is a duplicate copy of this sheet.

The filing fee has been calculated as shown below:


ITEM	CLAIMS		SMALL ENTITY	
	#	filed # extra		
Design application			\$155	
1. Basic utility app. fee				\$345
2. Total claims	16 - 20 =	x \$9 =		
3. Independent claims	2 - 3 =	x \$39 =		
	TOTAL FILING FEE =			\$345


☒ Check no. 1072 is enclosed to cover:

<input checked="" type="checkbox"/> Patent application filing fee	\$345
<input type="checkbox"/> Assignment recordation fee	
TOTAL	\$345

The Commissioner of Patents and Trademarks is hereby authorized to charge any additional fees which may be required, or credit any overpayment to Account No. 06-1985.

I hereby certify that this correspondence is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 CFR \$1.10 in an envelope addressed to: Assistant Commissioner for Patents, Washington, D.C. 20231, having Express Mail Label No. EM397112133US on March 30, 2000


Timothy T. Tyson, Reg. No: 28,915
Attorney for Applicant(s)


Timothy T. Tyson

Applicant or Patentee: ROGER E. SKOFF
Serial or Patent No:
Filed or Issued:
For: A WARNING SYSTEM

Docket No: 20/118

VERIFIED STATEMENT (DECLARATION) CLAIMING SMALL ENTITY
STATUS (37 CFR 1.9(f) and 1.27)

As a below named inventor, I hereby declare that I qualify as an independent inventor as defined in 37 CFR 1.9(c) for purposes of paying reduced fees under section 41(a) and (b) of Title 35, United States Code, to the Patent and Trademark Office with regard to the invention entitled A WARNING SYSTEM as described in

☒ the specification filed herewith
☐ application serial no. ___, filed ___.
☐ patent no. ___, issued ___.

I have not assigned, granted, conveyed or licensed and am under no obligation under contract or law to assign, grant, convey or license, any rights in the invention to any person who could not be classified as an independent inventor under 37 CFR 1.9(c) if that person had made the invention, or to any concern which would not qualify as a small business concern under 37 CFR 1.9(d) or a nonprofit organization under 37 CFR 1.9(e).

Each person, concern or organization to which I have assigned, granted, conveyed, or licensed or am under an obligation under contract or law to assign, grant, convey, or license any rights in the invention is listed below:

☒ no such person, concern, or organization
☐ persons, concerns or organizations listed below*

*NOTE: Separate verified statements are required from each named person, concern or organization having rights to the invention averring to their status as small entities.
(37 CFR 1.27)

FULL NAME

ADDRESS

☒ INDIVIDUAL ☐ SMALL BUSINESS CONCERN ☐ NONPROFIT ORGANIZATION

FULL NAME

ADDRESS

☒ INDIVIDUAL ☐ SMALL BUSINESS CONCERN ☐ NONPROFIT ORGANIZATION

FULL NAME

ADDRESS

☒ INDIVIDUAL ☐ SMALL BUSINESS CONCERN ☐ NONPROFIT ORGANIZATION

I acknowledge the duty to file, in this application or patent, notification of any change in status resulting in loss of entitlement to small entity status prior to paying, or at the time of paying, the earliest of the issue fee or any maintenance fee due after the date on which status as a small entity is no longer appropriate. (37 CFR 1.28(b))

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application, any patent issuing thereon, or any patent to which this verified statement is directed.

Roger E. Skoff

NAME OF INVENTOR

Signature of Inventor

Date

TITLE: A WARNING SYSTEM

INVENTOR: ROGER E. SKOFF

5

TECHNICAL FIELD

10 The present invention pertains generally to the field of alarm and warning systems such as those utilized to initiate and/or facilitate evacuation, and more particularly to a warning system that may contain one or a plurality of sensors and provides programmable warning and/or evacuation alarms and verbal instructions in the event of an emergency.

15

BACKGROUND ART

Warning and alarm systems for alerting people to emergency and other abnormal conditions are well known in the art. Such devices range from simple fire alarms to more complex systems which employ a plurality of sensing devices. All of these devices involve either a central system actuated by local sensors to "sound" local alarms, or are self-contained local units, which are and must only be independent of any overall system interaction. For example, U.S. Patent 3,798,672 shows a multiple condition sensing and audio warning system. The system includes a multi-track magnetic tape playing apparatus with a playback head selectively movable to any one of a plurality of track positions, an audio system connected to the output of the tape playing apparatus including speakers at selected locations, and a plurality of condition sensors each providing a signal representative of a condition being sensed. A control circuit is responsive to the condition signals and initiates operation of the tape playing apparatus. U.S. Patent 4,107,464 illustrates an alarm communication system which includes a circuit for normally transmitting music to a plurality of different locations within a building which includes a

20

25

30

source of music, a plurality of speakers selectively positioned throughout the building and a normally closed switch for connecting the source of music to each of the speakers. A source of programmed alarm announcements stored on tape is converted to an electrical signal, amplified and coupled to each of the speakers via an override switch. Actuation of the override switch in response to the occurrence of an emergency condition, such as fire, causes the normally closed switch to open and couple the electronic signal corresponding to the programmed alarm announcements to all of the speakers. U.S. Patent 4,288,789 defines an alarm system having a verbal message for monitoring mining operations, or the like. The system includes a plurality of first sensors each providing a signal representation of an abnormal condition being sensed, at least one additional sensor providing a signal representing an emergency condition being sensed, an oscillator and modulator for generating an emergency warning tone energized upon detection of the emergency condition, a plurality of speakers at selected locations for broadcasting the emergency warning tone, a multi-track tape player with playback head selectively movable to any one of the track positions and having an audio output connected to local and remote speakers, and circuit means effective to energize the tape player and move its head to an appropriate track containing a prerecorded oral message upon detection of an abnormal condition by one of the first sensors. U.S. Patent 4,415,771 discloses a public alert and advisory system for communication of emergency and/or other information from one or more central locations to a plurality of remote locations, such as by way of example, information regarding nuclear accident and evacuation procedures. The system utilizes conventional programming stations such as AM, FM or TV stations, central transmitting equipment, with emergency information being modulated by a second modulation technique different from the first modulation technique for ordinary programming so that conventional manually operated programming receivers will not be responsive to the emergency information. U.S. Patent 4,531,114 portrays an intelligent fire safety system which includes exit sign units having couplings to smoke sensor and heat sensor for input information, a speech synthesizer and strobe light to provide output information, and a communication unit to provide communication coupling between exit sign units on a single floor and between interfloor interfaces and a central monitoring unit. The exit sign

provides both a strobe light and a speech synthesizer which provides verbal instructions to floor occupants. U.S. Patent 4,682,348 comprises a life safety audio system having a voice synthesizer and a constant volume telephone network. The system has a plurality of detectors for detecting alarm conditions located throughout the building, a plurality of speakers located throughout the building, a source of pre-stored voice messages which can be broadcast over the speaker, and a telephone network. U.S. Patent 4,816,809 consists of a speaking fire alarm system which not only gives an alarm in voice on an occurrence of a fire, but also provides some information necessary for coping with the situation. The system includes a CPU, host computer, and voice synthesizer. U.S. Patent 5,074,137 describes a programmable atmospheric stabilizer which uses one or more sensors for detecting a condition of potentially hazardous material within a container or some other enclosed atmosphere. The sensors connect to a first threshold detector which activates a first order correcting device when the sensor detects a first order hazard. The sensor also connects to a second threshold detector which activates a second correcting device when the sensor detects a second order hazard. U.S. Patent 5,291,183 includes a multi-function alarming system which employs a vocoder which enables the alarm system to emit not only a buzzing sound but also a human voice. The alarm system has a microphone, a microphone amplifier, a vocoder, a memory, a preamplifier, a power amplifier and a speaker. U.S. Patent 5,349,338 depicts a fire alarm system having recorded vocal warning messages and/or instructions. The system has a microphone by which a user can record a vocal message specifically suited for a small child or adult in need of verbal instructions. U.S. Patent 5,663,714 shows a warning system for giving verbal instructions during a fire, comprising a smoke detector, a smoke detector output relay, a recording switch, a microphone, a digital recording and playback device, a timer/pulse generator, a pulse counter, a number of speakers, an amplifier and an alarm tone generator. U.S. Patent 5,724,020 illustrates a voice warning system for fire accidents which includes a plurality of fire sensors, a first multiplex selector, a detecting and scanning circuit, a locking circuit, a decoding circuit, a memory circuit, a second multiplex selector, a scanning circuit, a load, a time pulse controlling circuit, a fire emergency assistance calling circuit, and a plurality of loudspeakers which give fleeing instructions to

people in the building. U.S. Patent 5,990,796 defines a flash and voice warning system generally comprising a power supply with charging circuit, a smoke sensor power supply and auto reset circuit, a smoke sensor (or manual operation), a circuit for converting current to voltage, a single-chip microprocessor, a 60 Hz square wave generator, a control
5 circuit, a buffer, a current amplifier, a high-voltage circuit, N-discharge tube circuits, N-triggering circuits, a flash lamp direction control circuit, and a voice circuit.

DISCLOSURE OF INVENTION

The present invention is directed to a warning system which can detect any of one
5 or more emergency conditions and provide any or any combination of multiple
programmed responses thereto, each individually tailored to the specific type of
emergency at hand and the specific location of the actual warning device within the
system's area of operation. The warning systems includes a plurality of input trips which
sense emergency conditions in a local area. The warning system then issues
10 programmable emergency responses or alarms in the form of emergency lights, strobe
lights, and audio messages (verbal, a siren, a buzzer, etc.). The warning system is capable
of multiple responses (different sounds or messages, or combinations of sounds and
messages, or messages in different languages or multiple languages) triggered by, or in
response to, different emergency situations (fire, earthquake, explosion, intruders,
15 presence of smoke, radiation, noxious or poisonous gases, and the like). The warning
system is individually programmable to give differing specific instructions for evacuation
from specific locations within the protected area. The warning system is capable of
operation either individually or as part of a system for the protection of a larger area. If
used as part of an overall system, the evacuation devices can be "connected" to the system
20 either by direct wiring or by radio- or other remote control. If used as part of an overall
system, all of the covered devices will be capable of sensing the failure or destruction, or
disconnection by any means, of the central control device for the system of which they are
a part, and upon so doing, will immediately and independently commence alarm and the
issuance of preselected instructions.

25 In accordance with a preferred embodiment of the invention, a warning system
comprises a central control unit and a plurality of local units connected to the central
control unit, each of the local units having a plurality of input trips and a plurality of
programmable responses thereto; the plurality of input trips including a disconnect trip to
indicate that the central control unit or connection thereto has failed.

In accordance with an important aspect of the invention, the plurality of programmable responses include a warning output signal sent from the local unit to the central control unit to indicate the presence of a local emergency.

5 In accordance with an important feature of the invention, the warning output signal is also sent when a loss of local unit power is detected.

In accordance with another important aspect of the invention, the plurality of input trips may include a smoke detector, an earthquake detector, a noxious/poison gas detector, a proximity/motion intruder detector, a radiation detector, an explosion detector, or any other sensing device. A TV camera, a digital still camera, a microphone and/or
10 other video, photographic or audio monitoring device may also be included.

In accordance with another important feature of the invention, the plurality of programmable responses may include illumination of an emergency light, illumination of a strobe light, and the broadcast of an audio message (verbal, siren, buzzer, or the like).

In accordance with another important aspect of the invention, under emergency
15 conditions, the central control unit may broadcast either or both of (1) preselected audio, and (2) live voice instructions, to one or more local units of which the local trips have not been tripped. Also, the local units may be equipped with a microphone so that verbal messages may be sent to the central control unit.

Other features and advantages of the present invention will become apparent from
20 the following detailed description, taken in conjunction with the accompanying drawings, which illustrate, by way of example, the principles of the invention.

BRIEF DESCRIPTION OF DRAWINGS

FIG. 1 is a block diagram of a warning system in accordance with the present
5 invention; and,

FIG. 2 is a matrix showing conditions and responses thereto.

MODES FOR CARRYING OUT THE INVENTION

Referring initially to FIG. 1, there is illustrated a block diagram of a warning system in accordance with the present invention, generally designated as 20. Warning system 20 includes the following components:

CCU. Central Control Unit

LU. Local Unit (one or more)

- A_n.** Input Trips/Sensors;
- B.** Control Electronics (including operating and switching functions);
- C.** Bypass Relay;
- D.** Record/Playback Unit;
- E.** Emergency Light;
- F.** Strobe Light;
- G.** Amplifier;
- H.** Loudspeaker; and,
- I.** Battery.

Warning system 20 also includes the following signals:

- MI.** Music/Paging Input;
- DI.** Detector Input; and,
- WO.** Warning Output.

It may be appreciated that while only one local unit **LU** is shown in FIG. 1., a plurality of local units **LU**, each disposed in a different local area, may be connected to the central control unit **CCU**.

The central control unit **CCU** comprises the central monitoring and control station of warning system 20. A plurality of local units **LU** are connected to the central control unit **CCU** (either hardwired, by RF, or by other means). Each of the plurality of local units **LU** has a plurality of input trips **A_n** and a plurality of programmable responses thereto. The plurality of programmable responses for each local unit **LU** are tailorable to meet the needs of a particular location. Input trips **A_n** can include any number of

sensor/transducer devices that detect an emergency or abnormal condition. For example, input trip **A₂** could be a smoke detector, input trip **A₃** could be an earthquake detector, input trip **A₄** could be a proximity or motion detector, and input trip **A₅** could be a noxious or poison gas detector. Input trips could also include devices to sense AC power failure, heat sensors, radiation sensors, explosion sensors, or any other devices which could report the presence of an emergency or abnormal occurrence at the local unit **LU**. Audio, video, photographic or other monitoring devices could be included, along with various input trips **A_n**. The plurality of input trips **A_n** also includes a disconnect trip **A₁** which indicates that the central control unit **CCU** or connection thereto has failed. Disconnect trip **A₁** is activated by loss of the detector input **DI** signal which is sent to the local units **LU** from the central control unit **CCU**. Failure of this signal indicates failure, destruction, or disconnection, of the central control unit **CCU**. The signal sent to detector input **DI** may be DC, RF, IR, or any other convenient transmission format.

The plurality of programmable responses includes various alarms such as illumination of an emergency light **E**, illumination of a strobe light **F** (for the hearing impaired), and a plurality of audio messages (verbal voice messages broadcast in a plurality of different languages, siren, buzzer, etc.) as output from record/playback unit **D**. The exact number and content of the programmable responses is selectively controlled by the control electronics **B**. The plurality of programmable responses also includes a warning output **WO** signal which is sent from the local unit **LU** to the central control unit **CCU** to indicate the presence of a local emergency. In a preferred embodiment, the warning output **WO** signal is also sent when a loss of local unit **LU** power is detected.

Control electronics **B** contain all of the control, switching, programming, and operating circuitry necessary to initiate the desired emergency responses. Control electronics **B** cause the appropriate message from the record/playback unit **D** to be sent to amplifier **G** to power loudspeaker **H**. It may be appreciated that the present invention can be designed and programmed to provide any desired response to any number of emergency or abnormal conditions.

Record/playback unit **D** contains a plurality of pre-recorded emergency messages and instructions that are selected by the control electronics **B** depending upon the nature

of the emergency as detected by the input trips A_n . The record/playback unit can employ tape, IC-controlled, or any other recording and playback technology.

Under non-emergency conditions, the central control unit **CCU** broadcasts preselected audio **MI** (for example music and/or paging messages) to each of the local units **LU**. However, when one of input trips A_n is activated, the control electronics **B** cause bypass relay **C** to disconnect the preselected audio **MI**, and substitute the appropriate programmable response from the local unit **LU**. That is, loudspeaker **H** is driven by control electronics **B**, record/playback unit **D**, and amplifier **G**, rather than from music/paging input (preselected audio) **MI**. Concurrently, the warning output **WO** signal notifies the central control unit **CCU** that bypass relay **C** has been activated, thereby indicating a local emergency.

Amplifier **G**, loudspeaker **H**, and battery **I** comprise conventional readily available electronics technology.

In another preferred embodiment, if an emergency condition outside the area of the local unit **LU** is detected (i.e. no local input trip has been activated), it still may be desirable to broadcast emergency messages or instructions. In this instance, all alarms or instructions will come to the local unit **LU** from the **CCU** by way of the music/paging input **MI**. Also, the local units **LU** may be equipped with a microphone so that verbal messages may be sent to the central control unit **CCU**.

In another possible embodiment, local unit **LU** could operate as a stand alone system without the central control unit **CCU**.

FIG. 2 is a matrix showing various emergency conditions and possible programmed responses thereto. For example, if smoke is detected at a local unit **LU**, the emergency lights are illuminated, strobe lights are illuminated, the normal audio **MI** (e.g. music/paging) from the **CCU** is disconnected, an audio message (verbal, siren, buzzer, etc.) is broadcast, and a warning output **WO** signal is sent from the local unit **LU** to the central control unit **CCU** indicating that an emergency condition exists. In a preferred embodiment, if an intruder is detected by a proximity/motion input trip A_4 , no local response (e.g. emergency lights, strobe light, etc.) is directed, however the warning output **WO** signal is sent to the central control unit **CCU** in the form of a "silent alarm". If loss

of local unit **LU** power is detected, the warning output **WO** signal is also sent to the central control unit **CCU**. If failure or destruction of the central control unit **CCU** is detected through loss of the detector input **DI** signal, in a preferred embodiment all of the local unit **LU** response devices are activated.

5 In terms of physical construction, the present invention can be fabricated in three or more physical configurations. These are:

“EXIT SIGN” - Either one or two-sided, and may be mounted either in or on a wall or suspended from the ceiling or other support structure.

10 “BOX” - This may be mounted to a wall, bracket-mounted, or suspended from a ceiling or other support structure.

“FLUSH” - This will be flush-mounted (or possibly concealed, either for cosmetic or security reasons) in a wall or ceiling.

15 The preferred embodiments of the invention described herein are exemplary and numerous modifications, dimensional variations, and rearrangements can be readily envisioned to achieve an equivalent result, all of which are intended to be embraced within the scope of the appended claims.

I claim:

1. A warning system, comprising:

- 5 a central control unit;
 a plurality of local units connected to said central control unit;
 each of said plurality of local units having a plurality of input trips and a
plurality of programmable responses thereto;
 said plurality of programmable responses for each said local unit tailorable to
10 meet the needs of a particular location; and,
 said plurality of input trips including a disconnect trip indicating that said central
control unit has failed.

2. A warning system according to Claim 1, further including:

- 15 said plurality of programmable responses including a warning output signal sent
from said local unit to said central control unit which indicates the presence of a local
emergency.

3. A warning system according to Claim 2, further including:

- 20 said warning output signal being sent when a loss of local unit power is
detected.

4. A warning system according to Claim 1, further including:

- 25 said plurality of input trips including a smoke detector.

5. A warning system according to Claim 1, further including:

- said plurality of input trips including an earthquake detector.

6. A warning system according to Claim 1, further including:

- 30 said plurality of input trips including a motion detector.

7. A warning system according to Claim 1, further including:
said plurality of input trips including a noxious or poisonous gas detector.
- 5 8. A warning system according to Claim 1, further including:
said plurality of programmable responses including illumination of an emergency
light.
9. A warning system according to Claim 1, further including:
10 said plurality of programmable responses including illumination of a strobe light.
10. A warning system according to Claim 1, further including:
said plurality of programmable responses including the broadcast of an audio
message.
- 15 11. A warning system according to Claim 10, further including:
said audio message being a verbal message that is broadcast in a plurality of
different languages.
- 20 12. A warning system according to Claim 1, further including:
under non-emergency conditions, said central control unit broadcasting
preselected audio to each of said local units.
- 25 13. A warning system according to Claim 12, further including:
when one of said input trips is activated, said preselected audio is disconnected.
14. A warning system according to Claim 1, further including:
under emergency conditions, said central control unit allows for broadcasting at
least one of (1) preselected audio, and (2) live voice instructions to at least one of said
30 local units, of which no local trip has been tripped.

15. A warning system according to Claim 1, further including:

said plurality of programmable responses including a warning output signal sent from said local unit to said central control unit which indicates the presence of a local

5 emergency;

said warning output signal being sent when a loss of local unit power is detected;

said plurality of input trips including a smoke detector;

said plurality of input trips including an earthquake detector;

10 said plurality of input trips including a motion detector;

said plurality of input trips including a noxious or poisonous gas detector;

said plurality of programmable responses including illumination of an emergency light;

said plurality of programmable responses including illumination of a strobe light;

15 said plurality of programmable responses including the broadcast of an audio message;

under non-emergency conditions, said central control unit broadcasting preselected audio to each of said local units; and,

when one of said input trips is activated, said preselected audio is disconnected.

20

16. A warning system, comprising:

a central control unit;

a plurality of local units connected to said central control unit;

each of said plurality of local units including a plurality of input trips;

25 said input trips connected to control electronics;

said control electronics connected to a bypass relay;

said control electronics connected to a plurality of response devices;

said control electronics connected to a record/playback unit;

said record/playback unit connected to an amplifier;

30 said amplifier connected to a loudspeaker; and,

a battery pack connected to said plurality of input trips, said control electronics, and said amplifier.

ABSTRACT

A warning system (20) includes a central control unit (CCU), and a plurality of
5 local units (LU) connected to the central control unit (CCU). Each local unit (LU)
includes a plurality of input trips (A_n), such as smoke detector, an earthquake detector,
and gas detector, and a plurality of programmable responses, such as a bypass relay (C), a
message delivered by a record/playback unit (D), an emergency light (E), and a strobe
light (F). The input trips (A_n) also include a disconnect trip (A_1), which is activated by a
10 detector input signal (DI) sent from the central control unit (CCU), and indicates that the
central control unit (CCU) has malfunctioned. The programmable responses include a
warning output signal (WO) which is sent from the local unit (LU) to the central control
unit (CCU) to indicate the presence of a local emergency at the local unit (LU).

15

Fig. 1

20




Fig-2

CONDITION	RESPONSE				
	Emergency Light	Strobe Light	Normal Audio (MI) disconnected	Audio Message broadcast (WO)	Signal to CCU
SMOKE detected	YES	YES	YES	YES	YES
EARTHQUAKE detected	YES	YES	YES	YES	YES
PROXIMITY/ MOTION detected	NO	NO	NO	YES	YES
NOXIOUS/POISON GAS detected	YES	YES	YES	YES	YES
LOSS OF LOCAL POWER detected	NO	NO	NO	NO	YES
LOSS OF CCU detected (DI)	YES	YES	YES	YES	NO

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below.

I believe I am the original, first sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled A WARNING SYSTEM the specification of which

X is attached hereto.
_____ was filed on _____ as Application Serial No. _____
_____ and was amended on _____ (if applicable).

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above. I acknowledge the duty to disclose information which is material to the examination of this application in accordance with Title 37, Code of Federal Regulations, Section 1.56(a).

I hereby claim foreign priority benefits under Title 35, United States Code, §119 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

Number	Country	Date Filed	Yes	No
--------	---------	------------	-----	----

I hereby claim the benefits under Title 35, United States Code, §119(e) of any United States provisional application listed below:
Provisional application number _____ Date Filed _____

I hereby claim the benefit under Title 35, United States Code, §120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, §112, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, §1.56(a) which occurred between the filing date of the prior application and the national or PCT international filing date of this application:

Appl. Ser. No.	Filing Date	Status-patented, pending, abandoned
----------------	-------------	-------------------------------------

I hereby appoint the following to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith:

Timothy T. Tyson	Reg. No. 28,915	Leon D. Rosen	Reg. No. 21,077
Ted Masters	Reg. No. 36,209		

Address all telephone calls to: Timothy T. Tyson at (310) 477-0578
Address all correspondence to: Timothy T. Tyson
Freilich, Hornbaker & Rosen
10960 Wilshire Blvd., Suite 1220
Los Angeles, CA 90024

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under §1001 of Title 18 of United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Full name of sole or first inventor: Roger E. Skoff Citizenship: U.S.A.

Inventor's Signature ROGER E. SKOFF
Residence address: 10132 NORTHRIDGE DR.
RANCHO CUCAMONGA CA 91737 USA
Post Office Address: 9480 Utica Street, Suite 612
Rancho Cucamonga, CA 91730

Date 3/20/00